


The 550 is ideal for residential work and tight, confined spaces on commercial jobs. The accelerated RPM orbital cutting action delivers an efficient and operator friendly machine. With decibel ratings under industry and safety standards, this machine is a must-have.

ACCESSORIES


550-SIN

Model	550-SIN
Power Supply	Electric
Dimension	45cm x 108cm x 83cm (W x H x L)
Weight	55.8kg
Speed	1725rpm
Voltage	230V
Frequency	50Hz
Power	0.746kW/1Hp
Amps	14/7
Noise Emissions	73dB



ANGLE SHANK WITH CARBIDE TRIP

These shanks are designed for ceramic removal and thin set re-scraping. The 552 angle shank with carbide tip is designed for light-duty commercial and residential-grade ceramic tile and hard good removal.

552 / 4" x 2" x 0.312" (W x L x Thickness)



6280-500

SWIVE HEAD ATTACHMENT FOR RAZOR BLADES

Optional attachment keeps your blade in contact with the surface of the floor.

HEAVY-DUTY BLADES



These heavy-duty blades work on VCT, VAT, wood, tile, rubber, epoxy, elastomeric coatings, scraping thin-set and glued ceramic.

6285/ 3" x 6" x 0.094" (W x L x Thickness)

STANDARD BLADES



These heavy-duty blades are designed to remove soft goods, carpet and vinyl flooring. Their 0.062" thickness offers flexibility to maximize the shear point angle.

147/ 4" x 6" x 0.062" (W x L x Thickness)

PREMIUM HIGH-TEMPERED BLADES



They work on all glued-down carpets, VCT, VAT, rubber tile, cork and re-scraping adhesive and elastomeric coatings.

7050-202/ 3" x 10" x 0.062" (W x L x Thickness)

SELF-SCORING BLADES



These angled self-scoring work on attached cushion, unitary or secondary backing, vinyl back, soft to medium PVC, linoleum, carpet tiles, soft cork, enhancer and unibond hot melts.

6265-BD/3" x 8" x 0.094" (W x L x Thickness)



6280-505

SWIVEL HEAD ATTACHMENT

Optional swivel head attachment maintains 100 percent contact between the blade and the surface maximizing production rates. Rotate the head 180 degrees to self-sharpen the blade during use.

- holds blades of 0.062 or 0.094 thickness
- works on thin, soft coatings, paint, hard to remove gummy or dry adhesive.
- ultimate adhesive removal.


WKFS290

Floor hammer uses rigid structure holder to increase the stability and strength of the machine during operation. It provides the operator with comfort in performing chiseling operation on tile removal or surface screed removal. The bracket is adjustable with various angles to cater for different operations.


CEFH-150(V1)

Model	WKFS290	CEFH-150(V1)
Weight	86kg	74kg
Dimension (LxBxH)	720x420x310(mm)	900x590x950(mm)
Blow Per Minit	1410bpm	1450bpm
Shank Size	Hex 30	Hex 30
Power Supply Cord	single phase	single phase
Frequency	50-60Hz	50-60Hz
Voltage	220v	230v
Power	0.75kW	1240kW